

Product specification

Date:2013-12-05 Index: 2



Product: G 133UN

Description: Precoated Glass textile wall covering for indoor walls and ceilings.

Composition: Texturized yarn of glassfiber in warp.
Sliveryarn of glassfiber in weft.
Precoated soft touch coating

Technical data:


Properties	Unit	Min value	Nom value	Max value
Width	mm	990	1000	1010
Length deviation	m	-0		
Thickness	mm		0,6	
Total weight	g / m ²	122	136	150
Tensile strength				
Warp direction	N / 5cm	555	653	
Weft direction	N / 5cm	297	350	

Glue consumption Approx. 250 g / m². See also instructions on the glue bucket.

Paint consumption First coating Second coating
m² / litre 6,6

Facing side

Facing side is the **OUTSIDE** of the roll.



Reverse side marking

Continous gray line 23 cm from the rolls edge.

Pattern matching

Straight match - thread to thread.





Pick over warpthread against pick under warpthread

Allowed amount of marked spot faults

Roll length 15m Max 1
Roll length 25 & 30m Max 2
Roll length 50m Max 3

Note: A joint can occur in a roll and is considered as a spot fault.

Certificates:



Storing: -10 to +50 degrees Celcius
Use within 2 years after production

Information above is accurate to the best of our knowledge. Our products are subject to rigorous quality control along the production line to ensure conformance. Divergence within our tolerance may occur.

Preiss-Daimler Fibre Glass AB, Box 7013, S-250 07 Helsingborg. Tel +46 42 25 05 00, Fax + 46 42 16 01 42