

## MOTIP Deco Clear Lacquer

Ord.-no.: look at ordering information

## Technical Information



High quality clear lacquer to treat surfaces, treated and untreated, of wood, metal, aluminium, glass, stone, and various types of plastic.

### Quality & properties

- Lasting Gloss
- Excellent filling property.
- Scratch free and shock proof.
- Resistant to petrol, chemicals and weather influences
- Corrosion preventive
- Excellent adhesion

### Physical & chemical data

- Base: Alkyd resin
- Colourname: Transparent
- Degree of gloss:
  - ◊ high gloss, >85 GU
  - ◊ semi mat, 25 ±5 GU
- Efficiency:
  - ◊ 400 ML – 1,25 - 1,75 m<sup>2</sup>
  - ◊ 150 ml – 0,5 m<sup>2</sup>
- Dry to touch: 3 - 4 h
- Dust dry: 30 - 60 min
- Completely dry: 24 h
- Overcoatable: 24 h
- Surfaces: wood, metal, aluminium, glass, stone and various types of plastic
- Minimum Working Temperature: 15 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure:
  - ◊ 3500/20 bar
  - ◊ 2/20
- Flash point:
  - ◊ n.a.
  - ◊ 24
- Temperature Resistance: – 110 °C
- Content:
  - ◊ 400 ML
  - ◊ 150 ml
  - ◊ 100 ml

### How to use

- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.
- Apply the clear lacquer in several thin layers. Before applying the next layer, again shake the aerosol.
- Apply the clear lacquer in several thin layers. Before applying the next layer, again shake the aerosol
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).
- The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal**

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labeling**

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 55 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

**As of November 24, 2021** – This release replaces all eventually earlier issued versions.

**European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - [info-de\(at\)europaean-aerosols.com](mailto:info-de(at)europaean-aerosols.com)**  
**European Aerosols B.V., Wolframweg 2, NL-8471 XC Wolvega - [info-nl\(at\)europaean-aerosols.com](mailto:info-nl(at)europaean-aerosols.com)**